


#### "औद्योगिक, पर्यटकीय र हरित नगर, स्वच्छ, सुरक्षित र समृद्ध नगर"

### दमक नगरपालिका

### नगर कार्यपालिकाको कार्यालय



प.सं.: २०८०/०८१ सूचना शाखा च.नं.: दमक, झापा, कोशी प्रदेश, नेपाल



श्री सम्पूर्ण सूचीकृत सबै फर्महरु



बिषयः सूचीकृत भई दररेट पेश गर्ने सम्बन्धमा

(दोश्रो पटक प्रकाशित सूचना मितिः २०८१।०१।२७)

यस दमक नगरपालिकाको ३ नं. वडाको बिभिन्न स्थानहरुमा सि.सि.टिभी जडान गर्नुपर्ने भएकोले स्पेशिफिकेशन तथा BOQ अनुसारको सामाग्रीहरु खरिद गर्नुपर्ने भएको हुँदा मिति २०८१।०१।३१ गते सोमवार ४ बजे सम्ममा दमक नगरपालिकाको कार्यालयमा उपलब्ध गराइदिनुहुन सम्पर्ण सूचीकृत फर्महरुलाई अनुरोध छ। सोही दिन दिनको ४:१५ बजे दररेट खोलिने व्यहोरा समेत जानकारीको लागि अनुरोध छ।

समीप चुडल सूचना प्रविधि अधिकृत

#### आवश्यक कागजातहरूः

- फर्म दर्ता
- अघिल्लो आ.व. को कर चुक्ता
- भ्याट रजिस्ट्रेशन
- Filled Technical Specification Compliance Sheet

नोटः टेक्निकल स्पेशिफिकेशन दमक नगरपालिकाको वेबसाइट damakmun.gov.np मा राखिएको छ।

#### **Bill of Quantity (BOQ)**

To Damak Municipality, Office of Municipal Executive Damak, Jhapa Koshi Province, Nepal

Seal of the Firm:

Subject: Rate Submission for CCTV in Ward No. 3

Subject: Rate Submission for CCTV in W				Walu No. 3		
SN	Item	Unit	Qty	Unit Price	Unit Price in Words	Total
1	Electricity Concentric Cable 10mm	meter	550			
2	4MP IP Bullet Color Camera (4mm) Location: Baghkhor Chowk (3) Aamchowk(3), Dhukurpani Chowk 3, Golatar Chowk (3), Mawa Bridge(2)	pcs	14			
3	32 Channel 4K NVR	pcs	1			
4	Pole Mount Bracket Branded	pcs	14			
5	4 TB Survelliance Hard disk	pcs	1			
6	Installation( Water proof Junction Box(ABS Material size min 290*215mm, depth 84mm)-1pcs, 1 DPMCB 6A, Power Supply Unit(12V, 10A) 1pcs, and all other required items like cat6, electric wires etc)	site	5			
7	Optical Fiber Lease (GPON) (4 port ONU, Fiber Drop Cable, etc shall) and AMC Charge for 1 Year) 3 spot	Is	1			
	Total	ı	1	1		
	VAT 13%					
	Total with V	/AT				

VAT 13%	
Total with VAT	
Submitted By:	
Signature:	
Name of Designation of:	
Signatory:	
Firms Name:	

## "Industrial, Touristic and Green City, Clean, Safe and Prosperous City" Damak Municipality



## Office of the Municipal Executive Damak,Jhapa Koshi Province, Nepal



#### Technical Compliance Sheet for 4MP IP Bullet Cammer

SN	Parameters	Requirements	Compliance (Fully Compliant, Partially Compliant, Non Compliant) or Bidders Offer		
	Manufacture	To be filled by bidder			
	Brand	To be filled by bidder			
	Model No	To be filled by bidder			
1	Camera				
	Image Sensor	1/1.8" Progressive Scan CMOS			
	Max. Resolution	2688 × 1520			
	Min. Illumination	Color: 0.0005 Lux @ (F1.0, AGC ON), 0 Lux with white light			
	Shutter Speed	1/3 s to 1/100,000 s			
	Wide Dynamic Range	130 dB			
	Angle Adjustment	Pan: 0° to 360°, tilt: 0° to 90°, rotate: 0° to 360°			
2	Lens				
	Type	Fixed Focal Length, 4mm			
	Lens Type & FOV	4 mm, horizontal FOV 95°, vertical FOV 51°, diagonal FOV 115°			
	Aperture	F1.0			
3	DORI				
	DORI	4 mm, D: 77 m, O: 30 m, R: 15 m, I: 7 m			
4	Illuminator				
	White Light Range	60 m			
	Smart Supplement Light	Yes			
5	Video				
	Main Stream	50 Hz: 25 fps (2688 × 1520, 1920 × 1080, 1280 × 720) 60 Hz: 30 fps (2688 × 1520, 1920 × 1080, 1280 × 720)			
	Sub Stream	50 Hz: 25 fps (1280 × 720, 640 × 480, 640 × 360) 60 Hz: 30 fps (1280 × 720, 640 × 480, 640 × 360)			
	Video Compression	Main stream: H.265/H.264/H.265+/H.264+			
	Video Bit Rate	Sub-stream: H.265/H.264/MJPEG 32 Kbps to 8 Mbps			
	H.264 Type	Baseline Profile/Main Profile/High Profile			
	H.265 Type	Main Profile			
	Bit Rate Control	CBR/VBR			
	Scalable Video Coding (SVC)	H.264 and H.265 encoding			
	Region of Interest (ROI)	1 fixed region for main stream and sub-stream			
6	Network	1			
	Simultaneous Live View	Up to 5 channels			
	API	Open Network Video Interface (Profile S, Profile G, Profile T), ISAPI, SDK			
	Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP,IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP, WebSocket,			

T	Jser/Host	Up to 20 users. 3 user levels: administrator, operator and user	
		Password protection, complicated password, HTTPS encryption, IP address filter, Security Audit Log, basic and digest authentication for HTTP/HTTPS, TLS 1.1/1.2, WSSE and digest authentication for Open Network Video Interface	
1	Network Storage	NAS (NFS, SMB/CIFS), auto network replenishment (ANR)	
1	Web Browser	Supported Yes	
7 1	mage		
I	Day/Night Switch	Auto, Schedule	
I	mage Enhancement	BLC, HLC, 3D DNR	
S	mage Parameters Switch	Yes	
		Rotate mode, saturation, brightness, contrast, sharpness, gain, white balance adjustable by client software or web browser	
	Interface		
		Built-in memory card slot, support microSD/microSDHC/microSDXC/TF card, up to 512 GB	
I	Hardware Reset	Yes	
1 1 -	Communication nterface	1 RJ45 10 M/100 M self-adaptive Ethernet port	
9 Event			
		Motion detection (human and vehicle targets classification), video tampering alarm, exception	
		Line crossing detection, intrusion detection, region entrance detection, region exiting detection Scene change detection	
		Upload to NAS/memory card/FTP, notify surveillance center, trigger recording, trigger capture, send email	
10 I	Deep Learning Functi	ion	
F	Face Capture	Yes	
11 General			
F	Power	12 VDC ± 25%, 0.7 A, max. 8.5 W, Ø5.5 mm coaxial power plug PoE: 802.3af, 36 V to 57 V, 0.30 A to 0.18 A, max. 12 W	
1	Web Client Language	English	
		Anti-flicker, heartbeat, mirror, privacy mask, flash log, password reset via email	
		-30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less	
	Conditions Approval	(non-condensing)	
	EMC	Yes	
	Safety	Yes	
	Environment	yes	
H	Protection	IP67	
F	Protection	IP67	

## "Industrial, Touristic and Green City, Clean, Safe and Prosperous City" Damak Municipality Office of the Municipal Executive Damak,Jhapa Koshi Province, Nepal



#### Technical Compliance Sheet for 4K NVR 32 Channel

	Technical Compliance Sheet for 4K NVR	
Feature	Specification	Compliance (Fully Compliant, Partially Compliant, Non Compliant) or Bidders Offer
Manufacture, Country To filled by Bidder		
Brand Name To filled by Bidder		
Model No.	To filled by Bidder	
Video	H.265/ H.265+/ H.264+/ H.264	
Compression/Format	1 1 1000 1000/00 H 1000 1004/00 H 1000	
Video Output (VGA)	1-ch, 1920 1080/60 Hz, 1280 1024/60 Hz, 1280 720/60 Hz	
Video Output (HDMI) 1-ch, 4K (3840 2160)/30 Hz, 2K (2560 1440)/60 Hz, 1920 1080/60 Hz, 1280 1024/60 Hz, 1280 720/60 Hz, 1024 768/60 Hz		
Video Recording Res.	1920 x 1080	
Max. Video Recording Res.	3840 x 2160	
IP Video Input	32-ch	
Audio Input Channel (RCA)	1 Channel RCA	
Audio Compression	G.711ulaw/G.711alaw/G.722/G.726/AAC	
<b>Audio Output Channel</b>	1 Channel RCA	
Two way Audio	1-ch, RCA (Linear, 1 KΩ)	
Stream Type Video, Video & Audio		
Live View / Playback Resolution	12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF /2CIF/CIF/QCIF	
Decoding Capability	AI on: 1-ch@12 MP (30 fps)/2-ch@8 MP (30 fps)/4-ch@4 MP (30 fps)/8-ch@ 1080p (30 fps), AI off: 2-ch@12 MP (30 fps)/3-ch@8 MP (30 fps)/6-ch@ 4 MP (30 fps)/ 12-ch@1080p (30 fps)	
Synchronous Playback	16-ch	
Network Protocol	TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP, HTTP, HTTPS	
Number HDD Interface (SATA)	2 SATA	
Max HDD Support (GB,TB)	Up to 10TB capacity for each HDD	
Max. Storage Support 20TB		
Network Interface 1 RJ-45 10/100/1000 Mbps self-adaptive Ethernet		
(RJ45) interface USB Port Front panel: 1 x USB 2.0; Rear panel: 1 x USB 2.0		
Remote Connections	128	
Video Detection	Motion Detection 2.0	
<b>Power Supply</b>	12 VDC, 3.3 A	
Approx. Power Consumption	< 15 W (without HDD	
4		



# "Industrial, Touristic and Green City, Clean, Safe and Prosperous City" Damak Municipality Office of the Municipal Executive Damak,Jhapa Koshi Province, Nepal



#### Technical Compliance Sheet for 4TB Surveillance HDD

Feature, Specificati	Compliance (Fully Compliant, Partially Compliant, Non Compliant) or Bidders Offer	
Manufacture, Country	To filled by Bidder	
Brand Name	To filled by Bidder	
Model No.	To filled by Bidder	
Capacities	4TB / 4000GB	
Interface	SATA 6Gb/s	
FEATURES AND PERFORMANCE		
Drive Bays Supported	8+	
Cameras Supported	Up to 64	
Max Sustained Transfer Rate OD (MB/s)	190	
Hard Disk Rotational Speed	5900 RPM	
Cache (MB)	64	
RELIABILITY/DATA INTEGRITY		
Tarnish Resistant	Yes	
Load/Unload Cycles	300,000	
Nonrecoverable Read Errors Rate, Max	1 per 10E14	
Power-On Hours per year	8760	
Workload Rate Limit (WRL)	180	
Mean Time Between Failures (MTBF) (hours)	1M	
POWER MANAGEMENT		
Startup Current, Typical (12V, A)	1.8	
Average Operating Power (W)	5.5	
Idle Average (W)	3.2	
Standby Mode/Sleep Mode, Typical (W)	0.25/0.25	
Voltage Tollerance (5V)	±5%	
Voltage Tolerance (12V)	±10%	
ENVIRONMENTAL/TEMPERATURE		
Operating (ambient, min °C)	0	
Operating (drive case, max °C)	70	
Nonoperating (ambient, min °C)	-40	